

4230 TOWING TRACTOR

FOR LOGISTIC AND INDUSTRIAL APPLICATIONS

The Industrial Tow Tractor 4230 is equipped with a 30 hp Agrale engine that provides for low maintenance costs. Ideal for moving cargo and materials in airports, condominiums, hospitals, and logistic and industrial operations.



AGRALE

www.agrale.com.br

Instagram, Facebook, YouTube icons followed by [@agraleSA](#)

- Hydrostatic steering
- 30 hp engine
- Low fuel consumption
- Optional double wheels



4230 TOWING TRACTOR

Generated on 21/02/2020 21:13:21

ENGINE	
Brand / model	AGRALE M 790
No. of Cylinders	2 - Vertical in line
Aspiration	Natural
Power	25 CV
Maximum Power in PTO	27,0 cv (19,8 kW) @ 3.000 engine rpm
Maximum Torque	6,9 daNm - 7,0 kgf.m @ 2.550 rpm (NBR ISO 1585)
DRIVING TRANSMISSION	
Type	Mecânica
No. of Gears	6 Front/ 2 Reverse
Differential lock	NA
Front axle	Oscillating
CLUTCH	
Type	Simple dry disc
Drive	Mechanical
POWER TAKEOFF	
Drive	NA
Type / drive	NA
Nominal Speed	540 rpm @ 2.485 engine rpm
HYDRAULIC SYSTEM	
Pressure	NA
Maximum Flow	NA
Remote control	NA
Hitch	NA
Lift capacity	NA

BRAKES	
Service Brake	8 Wet discs oil bath
Parking Brake	Manual Lever
STEERING WHEEL	
Type	Hydrostatic
WHEELSETS	
Standard Front Tires	Aro: 4.00J x 15" / Pneu: 5.60 - 15"
Standard Rear Tires	Aro: 7.00 x 20" / Pneu: 9.00 - 20"
Optional Weelsets	Double rear wheels (9.00 - 20")
ELECTRIC SYSTEM	
Battery	12V 55 A.h
Alternator	14V 55 A
CAPACITIES	
Fuel Tank	39 L
DIMENSIONS	
Height	1314 mm
Front gauge	1120 mm
Rear Tread	1200 mm
Length	2870 mm
Width	1370 mm
WEIGHTS	
Shipping weight	1420 kg
Operating weight (curb weight)	1517 kg
OPTIONAL ITEMS	
Industrial draw bar, rear double wheels (9.00-20"), front guard, canopy, remote control valve, adjusting tread front axle, beacon light.	